


Glass Passivated Bridge Rectifiers

LBS Package



PINNING

PIN	DESCRIPTION
1	Input Pin (~)
2	Input Pin (~)
3	Output Anode (+)
4	Output Cathode (-)

Features

- Glass Passivated Chip Junction
- Reverse Voltage - 1000 V
- Forward Current - 6.0 A
- High Surge Current Capability
- Designed For Surface Mount Application

Benefits

- Case:Molded plastic
- Terminals:Platde leads solderable per MIL-STD-750,Method 2026
- Polarity:Polarity symbols molded or Marked on body
- Mounting Position:Any

Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter		Symbols	LBS60M		Units
Maximum Repetitive Peak Reverse Voltage		VRRM	1000		V
Maximum RMS voltage		VRMS	700		V
Maximum DC Blocking Voltage		VDC	1000		V
Average Rectified Output Current		Io	6.0		A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)		IFSM	170		A
Rating for fusing(t<8.3ms)		i ² t	120		A ² sec
Instantaneous forward voltage per diode@25 °C		VF	TYP.	MAX.	V
	IF=1A		0.90	--	
	IF=3A		0.98	1.00	
Maximum DC Reverse Current @TA=25 °C at Rated DC Blocking Voltage @TA=125 °C		IR	5 100		μA
Operating and Storage Temperature Range		Tj, Tstg	-55 ~ +150		°C
Typical thermal resistance (Note 2)		RthJC RthJA RthJL	10 68 22		°C/W

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)

FIG.1 Derating Curve Output Rectified Current




FIG.2 Typical Forward Characteristics per Diode




FIG.3 Maximum Non-Repetitive Peak Forward Surge Current per Diode







FIG.4 Typical Reverse Characteristics per Diode




PACKAGE OUTLINE DIMENSIONS



LBS		
Dim	Min	Max
A	10.05	10.35
B	7.00	7.40
C	9.75	10.05
D	5.25	5.60
E	1.70	1.90
F	0.45	0.95
G	0.00	0.20
H	1.45	1.80
h	1.45	1.65
K	0.15	0.35




Suggested PCB printfoot layout



Unit: inches (mm)


Marking Information



①W : Company's trademark


②Product model : LBS60M

③PDC information:





Packaging Information


1.Reel Dimensions



2. Inside Box



3. Outside Box



Packaging Information

NO	UNIT	Reel Dimensions			Inside Box			Outside Box		
Size	mm	φ	A	B	L1	W1	H1	L2	W2	H2
		331	110	28	340	340	43	360	360	270
QTY	PCS	Smallest package,2,500PCS/reel			2,500PCS,1 reel in total			15,000PCS/carton,6boxes in total		
Note	Tolerance ≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm									