


MUR1660CTR-A

MUR1660CTFR-A



18-Jun-2020

Superfast Recovery Rectifier

TO-220AB
MUR1660CTR-A



TO-220F
MUR1660CTFR-A



Features

- Low forward voltage drop
- Low leakage current
- High current capability
- Super fast switching speed
- High forward surge capability
- High reliability

Mechanical Data

- Epoxy: UL 94V-O rate flame retardant
- Lead: lead solderable per MIL-STD-202, method 208 guaranteed
- Mounting position: Any

Parameter	Symbols	MUR1660CTR-A	MUR1660CTFR-A	Units
Maximum Repetitive Peak Reverse Voltage	VRRM	600		V
Maximum RMS voltage	VRMS	420		V
Maximum DC Blocking Voltage	VDC	600		V
Maximum Average Forward Rectified Current	I(AV)	16.0		A
Reverse Recovery Time. IF=0.5A,IR=1A,IRR=0.25A	Trr	35		ns
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	IFSM	140		A
I ² t rating for fusing (1ms< t < 8.3ms)	I ² t	81		A ² S
Instantaneous Forward Voltage per Diode@TA=25 °C	VF	Typ	Max	V
		IF=2A	--	
		IF=8A	1.70	
Maximum DC Reverse Current @TA=25 °C at Rated DC Blocking Voltage @TA=125 °C	IR	5 50		μA
Operating and Storage Temperature Range	Tj, Tstg	-55 ~ +150		°C
Typical thermal resistance (Note 1)	RthJC	2.5	3	°C/W

Note: 1. Thermal resistance junction to case, lead and ambient in accordance with JESD-51.
Unit mounted on glass-epoxy substrate with 1oz/ft²_20x20 mm copper pad per pin with heatsink

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS





FIG. 4 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



MUR1660CTR-A


MUR1660CTFR-A

18-Jun-2020


PACKAGE OUTLINE DIMENSIONS

Note:unit In(mm)

TO-220AB



TO-220F




MUR1660CTR-A


MUR1660CTFR-A

18-Jun-2020

Marking Information



- ①W : Company's trademark
- ②Product model : MUR1660CTR or MUR1660CTFR
- ③PDC information:



- ④  Double wafer