



Superfast Recovery Rectifier

MURE3040PT

TO-247



Features

- Low forward voltage drop
- Low leakage
- High current capability
- Super fast switching speed
- High forward surge capability
- High reliability.

Mechanical Data

- Epoxy: UL 94V-O rate flame retardant
- Lead: lead solderable per MIL-STD-202, method 208 guaranteed
- Polarity: Color band denotes cathode end
- Weight: 5.65 grams

Parameter	Symbols	MURE3040PT	Units
Maximum Repetitive Peak Reverse Voltage	VRRM	400	V
Maximum RMS voltage	VRMS	280	V
Maximum DC Blocking Voltage	VDC	400	V
Maximum Average Forward Rectified Current	I(AV)	30.0	A
Reverse Recovery Time. IF=0.5A, IR=1A, IRR=0.25A	Trr	35	ns
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	IFSM	300	A
Max Forward Voltage at 15A and 25 °C	VF	1.30	V
Max Forward Voltage at 15A and 125 °C		1.15	
Maximum DC Reverse Current @TA=25 °C at Rated DC Blocking Voltage @TA=100 °C	IR	10 500	μA
Typical Junction Capacitance (Note1)	Cj	50	pF
Operating and Storage Temperature Range	Tj, Tstg	-55 ~ +150	°C
Typical thermal resistance (Note 2)	RthJC	1.5	°C/W

Note: 1. Measured at 1MHz and applied reverse voltage of 4 VDC.

2. Thermal resistance junction to case, lead and ambient in accordance with JESD-51.

Unit mounted on glass-epoxy substrate with 1oz/ft² 20x20 mm copper pad per pin with heatsink

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS






FIG. 4 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



PACKAGE OUTLINE DIMENSIONS

Note: unit: mm

TO-247



Dimensions in millimeters